

Machine Data Sheet

Machine: 1032	WM280V
<u>Product Dimensions:</u>	
Weight	220kg
Length x Width x Height	1380 x 675 x 520mm
Tray Length x Width	1270 x 420mm
<u>Shipping Dimensions</u>	
Length x Width x Height (no DRO)	1410 x 705 x 635mm
Length x Width x Height (DRO version)	1410 x 705 x 635mm
<u>Power/Motor</u>	
Motor size	1.5kw
Power Transfer (GH) gearbox or (VS) variable speed	VS
Spindle speeds (No: and achievable speeds)	(2) 30-450 / 150-2500rpm
Voltage (240v single) (440v 3 Phase)	240v Single
Fitment (Plug connection type)	3 Pin Plug
Current	50Hz 6.4A
<u>Main Specifications</u>	
Maximum swing	280mm
Centre height	140mm
Distance between centre's	680mm
Longitudinal travel (Z)	440mm
Cross slide travel (X)	170mm
Top slide travel (fine Z)	70mm
Spindle taper	MT4
Tailstock Taper	MT2
Tailstock quill travel	85mm
Spindle Bore	26mm
Tool shank size recommended for C/L	12mm
Metric and imperial threads	Yes
Chuck mount	Flange
Spindle Bearings /Drive	Taper roller bearings
<u>Other Specifications</u>	
Country of origin	China
Warranty	12 Months
Approximated assembly and setup time	30 mins
CE approved Certificate	Yes, available upon request

Machine Data Sheet

Additional products	
Optional stand	3214DL
Optional Digital Read Out Kit	8123
X scale	5105 - 200mm
Z Scale	5110 - 450mm
Chuck mount sizes	A= 52 Taper B=102 C=74.5 D=11mm
Base/tray fixing holes dimensions A-B-C-D	A= 157 B= 210 C=830 D=76 mm

